

SAFETY DATA SHEET**Primer**

The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued 04.10.2017

Revision date 23.09.2020

1.1. Product identifier

Product name Primer

UFI C610-E0K9-H00X-VGWA

Article no. 10500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance / preparation Impregnating and priming of felt and concrete roofs.

Relevant identified uses
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU19 Building and construction work
SU21 Consumer uses: Private households (= general public = consumers)
PC1 Adhesives, Sealants
PC9 Coatings and Paints, Fillers, Putties, Thinners

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name Auson AB

Postal address Verkstadsgatan 3

Postcode S-434 42

City KUNGSBACKA

Country SVERIGE

Telephone number +46 300-562000

Fax +46 300-562021

Email nina.nyth@auson.se

Website <http://www.auson.se/>

Contact person Nina Nyth

1.4. Emergency telephone number

Emergency telephone	Telephone number: 112 Description: SOS Alarm
---------------------	-------------------------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP / GHS]	Flam. Liq. 3; H226 STOT SE 3; H336 EUH 066
Additional information on classification	See section 16 for explanation of hazard statements (H) listed above.

2.2. Label elements

Hazard pictograms (CLP)



Composition on the label	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1% ~ 50 %, Oxidized bitumen ~ 50 %
Signal word	Warning
Hazard statements	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 261 Avoid breathing vapours. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents at hazardous or special waste collection point.
Supplemental label information	EUH 066 Repeated exposure may cause skin dryness or cracking.
EC label	Yes
VOC	Product subcategory : Binding primer Relevant VOC limit values: 750 g/l Maximum content of VOC: 396 g/l

2.3. Other hazards

Hazard description, general	Flammable
Other hazards	None

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents	Notes
-----------	----------------	----------------	----------	-------

Naphtha (petroleum) , hydrotreated heavy, benzene < 0,1%	CAS No.: 64742-48-9 EC No.: 919-857-5 Index No.: 649-327-00-6 REACH Reg. No.: 01-2119463258-33-xxxx	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 EUH 066	~ 50 %	1
Oxidized bitumen	CAS No.: 64742-93-4 EC No.: 265-196-4 REACH Reg. No.: 01-2119498270-36-0027		~ 50 %	

¹Substance classified with a health or environmental hazard

Remarks, substance	See section 16 for explanation of hazard statements (H) listed above.
Substance comments	H304 is not required on the label due to the product's viscosity.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Fresh air and rest.
Skin contact	Wash the skin with water and soap. Remove contaminated clothing. Get medical advice if discomfort develops.
Eye contact	Flush immediately with water for at least 5 minutes. Keep eye wide open while flushing. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING! Immediately consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

General symptoms and effects	No further relevant information available.
------------------------------	--------------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Specific details on antidotes	No information available.
-------------------------------	---------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical, foam or carbon dioxide (CO ₂).
Improper extinguishing media	Do not use a direct water jet that could spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards	Burning material may cause toxic vapours.
----------------------------	-------------------------------------------

5.3. Advice for firefighters

Personal protective equipment	Breathing apparatus should be used in fire fighting.
Other information	Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal protection measures Use the specified protective equipment. Keep unauthorized personnel away.

6.2. Environmental precautions

Environmental precautionary measures Do not allow spill to enter sewers or watercourses. Inform appropriate authorities if large amounts are involved.

6.3. Methods and material for containment and cleaning up

Clean up Collect with absorbent, non-combustible material into suitable containers. Destroy according to applicable regulations.

6.4. Reference to other sections

Additional information See Section 8 and section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling Wear prescribed personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed. Keep away from ignition sources. Store in original container.

Conditions to avoid Heating forms toxic gases.

7.3. Specific end use(s)

Specific use(s) See Section 1.2

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Substance	Identification	Exposure limits	TWA Year
Naphtha (petroleum) , hydrotreated heavy, benzene < 0,1%	CAS No.: 64742-48-9	Limit value (8 h) : 50 ppm Limit value (8 h) : 300 mg/ m ³ Limit value (short term) Value: 100 ppm Limit value (short term) Value: 600 mg/m ³	TWA Year: 2011
Control parameters comments	List source(s): EU - Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.		

DNEL / PNEC

Summary of risk management measures, human	No information available.
Summary of risk management measures, environment	No information available.

8.2. Exposure controls**Safety signs****Precautionary measures to prevent exposure**

Appropriate engineering controls	No smoking, fire, sparks or welding. Eyewash facilities should be available at the workplace. Keep containers closed, as much as possible. Provide good ventilation.
----------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

Eye / face protection

Suitable eye protection	Wear approved, tight fitting safety glasses where splashing is probable.
-------------------------	--------------------------------------------------------------------------

Hand protection

Skin- / hand protection, short term contact	Protective gloves must be used if there is a risk of direct contact or splashes.
Suitable materials	Nitrile rubber.
Breakthrough time	Value: > 8 hour(s) Comments: Change protective gloves regularly in order to avoid penetration problems.
Thickness of glove material	Value: $\geq 0,38$ mm

Skin protection

Skin protection remark	Protective clothing as needed.
------------------------	--------------------------------

Respiratory protection

Respiratory protection necessary at	In case of inadequate ventilation wear respiratory protection.
Recommended respiratory protection	Filter apparatus type: Respirator with A filter (brown).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Viscous liquid.
Colour	Black.
Odour	Characteristic.

Odour limit	Comments: Not applicable.
Melting point / melting range	Comments: Not applicable.
Boiling point / boiling range	Value: > 150 °C
Flash point	Value: 40 °C
Explosion limit	Value: 1 - 7 %
Density	Value: 900 kg/m ³ Temperature: 20 °C
Solubility	Comments: Soluble in organic solvents.
Partition coefficient: n-octanol/ water	Comments: No data available

9.2. Other information

Other physical and chemical properties

Comments	No further relevant information available.
----------	--------------------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Keep away from heat / sparks / open flames / hot surfaces. – No smoking.
------------	--------------------------------------------------------------------------

10.2. Chemical stability

Stability	Stable with normal handling.
-----------	------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No hazardous reactions known.
------------------------------------	-------------------------------

10.4. Conditions to avoid

Conditions to avoid	No information available.
---------------------	---------------------------

10.5. Incompatible materials

Materials to avoid	No hazardous reactions known.
--------------------	-------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	No formation of hazardous decomposition products are expected under normal conditions.
----------------------------------	----------------------------------------------------------------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Acute toxicity	Effect tested: LD50 Route of exposure: Oral

Value: > 2000 mg/kg
Animal test species: Rat

Effect tested: LD50
Route of exposure: Dermal
Value: > 2000 mg/kg
Animal test species: Rabbit

Effect tested: LC50
Route of exposure: Inhalation.
Duration: 4h
Value: > 5000 mg/m³
Animal test species: Rat

Other information regarding health hazards

Acute toxicity, human experience	No aspiration hazards known.
Skin corrosion / irritation, human experience	Repeated exposure may cause skin dryness or cracking.
Eye damage or irritation, human experience	Reliable information on eye effects is lacking. There is no reason to suspect such effects, but handle it with care and report any symptoms or injuries to the manufacturer or the distributor
General	Solvent vapours may evaporate from the product.
Inhalation	Headache. Dizziness. Indisposition.
Skin contact	Defats the skin. Prolonged or repeated contact may cause irritation.
Eye contact	May irritate the eyes.
Ingestion	Abdominal pains. Vomiting. Causes similar symptoms as by inhalation.
Assessment of germ cell mutagenicity, classification	The chemical structure does not suggest a mutagenic effect.
Carcinogenicity, other information	Does not present any cancer or reproductive hazards.
Reproductive toxicity	The chemical structure does not suggest such an effect.
Specific target organ toxicity - single exposure, human experience	May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Aquatic toxicity, fish	Value: > 100 mg/L Test duration: 96h Method: LC50
Substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Aquatic toxicity, algae	Value: > 100 mg/L Test duration: 72h Method: EC50

Substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Aquatic toxicity, crustacean	Value: > 100 mg/L Test duration: 48h Method: EC50
Ecotoxicity	Ecotoxicity data are not known for this product.

12.2. Persistence and degradability

Persistence and degradability description/evaluation	Not readily degradable.
------------------------------------------------------	-------------------------

12.3. Bioaccumulative potential

Bioaccumulation, comments	Has the potential to bioaccumulate.
---------------------------	-------------------------------------

12.4. Mobility in soil

Mobility	Expected to have relatively low mobility in soil.
----------	---------------------------------------------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	The product does not contain any PBT or vPvB substance.
------------------------------------	---------------------------------------------------------

12.6. Other adverse effects

Additional ecological information	Does not cause long term adverse effects in the aquatic environment.
-----------------------------------	----------------------------------------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate methods of disposal for the chemical	Destroy according to applicable regulations. Do not allow outlets to sewer or watercourse.
Appropriate methods of disposal for the contaminated packaging	Containers with liquid residues are hazardous waste. Empty containers should be transported to local recycling facility or waste treatment facility.
EWC waste code	EWC waste code: 170302 bituminous mixtures other than those mentioned in 17 03 01 Classified as hazardous waste: Yes
EWL packing	Classified as hazardous waste: No
Other information	EWC code is only a suggestion, final consumer selects a suitable EWC code.

SECTION 14: Transport information

Dangerous goods	Yes
-----------------	-----

14.1. UN number

ADR/RID/ADN	1139
IMDG	1139
ICAO/IATA	1139

14.2. UN proper shipping name

Proper shipping name English ADR/RID/ADN	COATING SOLUTION
Technical name/Danger releasing substance English ADR/RID/ADN	Petroleum products
ADR/RID/ADN	COATING SOLUTION
Technical name/danger releasing substance ADR/RID/ADN	Petroleum products
IMDG	COATING SOLUTION
Technical name/danger releasing substance IMDG	Petroleum products
ICAO/IATA	COATING SOLUTION
Technical name/danger releasing substance ICAO/IATA	Petroleum products

14.3. Transport hazard class(es)

ADR/RID/ADN	3
Classification code ADR/RID/ADN	F1
IMDG	3
ICAO/IATA	3

14.4. Packing group

ADR/RID/ADN	III
IMDG	III
ICAO/IATA	III

14.5. Environmental hazards

ADR/RID/ADN	No
IMDG	No

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

Product name	COATING SOLUTION
--------------	------------------

Additional information

Hazard label ADR/RID/ADN	3
Hazard label IMDG	3
Hazard label ICAO/IATA	3

ADR/RID Other information

Tunnel restriction code	D/E
-------------------------	-----

Limited quantity	ADR-S: The products are not comprised by the regulations in ADR-S according to section 2.2.3.1.5 or IMDG according to section 2.3.2.5.
Transport category	3
Hazard No.	30
Other applicable information ADR/ RID	30

IMDG Other information

EmS	F-E, <u>S-E</u>
Limited quantity	In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code but both full documentation and placarding of the cargo transport units is still required.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

EEC-directive	2006/121/2006
Biocides	No
Nanomaterial	No
References (laws/regulations)	The product is classified and labelled in accordance with EEC guidelines or national legislation.
Legislation and regulations	Regulation (EC) nr. 2015/830 Regulation (EC) nr. 1272/2008.

15.2. Chemical safety assessment

Chemical safety assessment performed	No
--------------------------------------	----

SECTION 16: Other information

Supplier's notes	These data are based on our best knowledge to date, however they do not imply any guarantee on the properties or quality of the product. In case of uncertainties we advise you to make own tests or ask for written directions from us.
List of relevant H-phrases (Section 2 and 3)	EUH 066 Repeated exposure may cause skin dryness or cracking. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness.
Version	8
Expired date	23.09.2023